UNYTOUCH
MANUFACTURING

Modular All In One

U41-P150UR-PDC

LCD
15 inches

BRIGHTNESS
250 cd/m2

PROCESSOR
Pentium Dual Core
3.0GHz

MEMORY
2GB DDR3

HARD DRIVE
250GB SATA

Unytouch Manufacturing is proud to present a completely new, versatile approach to All in One terminal's.

Addressing key drivers such as performance, durability and cost the Unytouch Modular All in One is well suited for both touch and non touch applications. Featuring a unique quick disconnect PC design, multiple I/O ports and a stable UMount base, the Unytouch Modular All In One makes the most of your digital world.

KEY FEATURES

- Intel Pentium Dual Core, 3.0GHz
- Rugged metal enclosure
- Stable Base With Bolt Down Option
- Multiple I/O – 4 USB, 1 Serial, 1 Parallel
- Easily Accessible I/O
- 3yr Warranty

UNYTOUCH
MANUFACTURING

Modular All In One

U41-P150UR-PDC

PC SPECIFICATIONS	
CPU	Intel Pentium Dual Core, 3.0GHz
Socket	775
FSB	800MHz
Hard Drive	250 GB
Hard Drive Interface	SATA
Memory	Number of slots: 2 (240 Pin DIMM) Installed Memory: 2GB Maximum Memory: 8GB
Graphics	Intel X4500
Audio	6 CH Intel HD Audio
Network	10/100/1000
I/O Ports	4 USB 2.0 1 Serial 1 DVI 1 VGA 1 RJ 45 Network 1 PS2 Keyboard 1 Parallel 3 Audio Jacks: Line in, Line out, Mic in
MONITOR SPECIFICATIONS	
LCD Panel	15" TFT LCD Active Matrix Display
Resolution	1024 x 768
Contrast Ratio	1000:1
Brightness	250 cd/m²
Response Time	8 ms
Pixel Pitch	0.297 mm x 0.297mm
Plug & Play	DDC 2B Compliance
OSD (On Screen Display)	Auto Tune, Brightness, Contrast, clock, Phase, H-position, V-position, Recall
Touch Technology	Standard 5 Wire Resistive, Optional SAW, Capacitive
Touch Interface	Dual Serial/USB
Built-in Speakers	Yes
Operating Enviroment	0 °C - 40 °C (32 °F - 104 °F) 10%-80% (no condensation)
Storage Conditions	-20 °C - 50 °C (-4 °F - 140 °F) 10%-90% (no condensation)
Package Dimensions (W x H x D)	530 mm x 530 mm x 300 mm
Weight	30 Lbs (13.6 Kg)
Stand Style	Umount
Mounting Option	Desktop Placement, Bolt Down & VESA Mountable
Monitor Tilting Degree	0° - 40°
Viewing Angle	75°/75°/70°/60°(L/R/U/D)
MTBF	50,000
PC Video Interface	Analog RGB (VGA)
Horizontal Scan Rate	30-60 Khz
Vertical Scan Rate	56-75 Hz
Display Mode	VGA 720 x 400 (70 Hz) VGA 640 x 480 (60/66/70/72/75 Hz) SVGA 800 x 600 (60/70/72/75 Hz) XGA 1024 x 768 (56/70/75 Hz) SXGA 1280 x 1024 (60/70/75 Hz)
OSD Control	Power On/Off with LED, Menu, Auto Tune, Adjustment (+/-)
Electrical Power	Adapter Input: 100 - 240 VAC, 50 - 60 Hz, Adapter Output: 19 VDC, 50 - 60Hz
Power Consumption	30 W (max)
Certification	CE , UL, FCC